



 **LIVE**

T5/54W SLS HF fluorescent light bar

Convincing rimless lightpower



The extremely compact 1LIVE fluorescent light bar features a high power and rimless light by using the new seamless T5 54W SLS tube. An optional adapter is available for the use of conventional T5 54W tubes. A genuine Swiss Quality all-rounder in a very well-considered housing.

Drive:

- DMX 512 USITT protocol
- Hybrid multi-core cable (power/data) for simple connectivity

Control:

- VIP-90 HF technology for uniform 0-100%
- Internal 16-bit resolution (65,536 levels)
- Significant reaction time of just 0.02 seconds

Protection functions:

- permanent electrode and temperature monitoring
- active current limiter
- Low and high voltage protection

Ventilation:

- Convection cooling, no fan

Lighting:

- T5 54W SLS, free lamp selection thanks to auto-parametrization
- conventional T5 54W with adapter possible



Electrical data:

- 230VAC +/- 10% ; 50 Hz
- Power consumption at full load: 60 W
- Power factor: > 0.98

Mechanical data:

- Aluminum housing with reinforced M10 suspension points
- Size: 1178 x 50 x 80mm (L x W x H)
- Weight: 4.1 kg

Conformity:

- EN 61347-1, EN 61000-4-2, EN 55015, EN 6100-3-2



Live-Light GmbH

Dorfstrasse 56
6332 Hagendorn
+41 (0)41 558 14 58

kontakt@live-light.ch
www.live-light.ch



POWERED BY

